

Three Phase String Inverter

SUN- 70 / 80 / 90 / 100 / 110 K-G03



Max. 6 MPP trackers, Max. efficiency up to 98.7%



Zero export application, VSG application



String intelligent monitoring (optional)



Wide output voltage range



Anti-PID function (Optional)



Type II DC/AC SPD

Deye

Stock Code: 605117.SH

Model	SUN-70K-G03	SUN-80K-G03	SUN-90K-G03	SUN-100K-G03	SUN-110K-G03
Input Side					
Max. DC Input Power (kW)	91	104	135	150	150
Max. DC Input Voltage (V)	1000				
Start-up DC Input Voltage (V)	250				
MPPT Operating Range (V)	200~850				
Max. DC Input Current (A)	40+40+40+40		40+40+40+40+40+40		
Max. Short Circuit Current (A)	60+60+60+60		60+60+60+60+60+60		
Number of MPPT / Strings per MPPT	4/4		6/4		
Output Side					
Rated Output Power (kW)	70	80	90	100	110
Max. Active Power (kW)	77	88	99	110	121
Nominal Output Voltage / Range (V)	3L/N/PE 380V/323V-418V, 400V/340V-440V				
Rated Grid Frequency (Hz)	50 / 60 (Optional)				
Operating Phase	Three phase				
Rated AC Grid Output Current (A)	101.5	115.9	130.4	144.9	159.4
Max. AC Output Current (A)	111.6	127.5	143.5	159.4	175.4
Output Power Factor	0.8 leading to 0.8 lagging				
Grid Current THD	<3%				
DC Injection Current (mA)	<0.5%				
Grid Frequency Range	47~52 or 57~62 (Optional)				
Efficiency					
Max. Efficiency	98.7%				
Euro Efficiency	98.3%				
MPPT Efficiency	>99%				
Protection					
DC Reverse-Polarity Protection	Yes				
AC Short Circuit Protection	Yes				
AC Output Overcurrent Protection	Yes				
Output Overvoltage Protection	Yes				
Insulation Resistance Protection	Yes				
Ground Fault Monitoring	Yes				
Anti-islanding Protection	Yes				
Temperature Protection	Yes				
Integrated DC Switch	Yes				
Remote software upload	Yes				
Remote change of operating parameters	Yes				
Surge protection	DC Type II / AC Type II				
General Data					
Size (mm)	838W×568H×323D				
Weight (kg)	73.7				
Topology	Transformerless				
Internal Consumption	<1W (Night)				
Running Temperature	-25~65°C, >45°C derating				
Ingress Protection	IP65				
Noise Emission (Typical)	<55 dB				
Cooling Concept	Smart cooling				
Max. Operating Altitude Without Derating	2000m				
Warranty	8 years				
Grid Connection Standard	CEI 0-21, VDE-AR-N 4105, NRS 097, IEC 62116, IEC 61727, G99, G98, VDE 0126-1-1, RD 1699, C10-11				
Operating Surroundings Humidity	0-100%				
Safety EMC / Standard	IEC/EN 61000-6-1/2/3/4, IEC/EN 62109-1, IEC/EN 62109-2				
Features					
DC Connection	MC-4 mateable				
AC Connection	IP65 rated plug				
Display	LCD 240 × 160				
Interface	RS485/RS232/Wifi/LAN				